













Qualität	Grammatur (g/m²)	Stärke (µm)	Bedruckbarkeit					
								
TRITEX L								
5085 BQ*	196	143			•	•		
515 a	132	141	•	•	•			•
525 a	137	148	•	•	•			•
555	175	175	•	•	•			•
575*	210	205	•	•	•			•
5105	245	225	•	•	•			•
737*	195	173	•	•	•			•
7107 c*	285	230	•	•	•			•
101010*	345	355	•	•	•			•
TRITEX SD								
222 cream*	80	89	•	•	•			
242*	97	111	•	•	•			
535*	138	160	•	•	•			
545	141	160	•	•	•			
575 a	168	192	•	•	•			
5085*	133	250	•	•	•			
7087*	166	135	•	•	•			
747*	181	210	•	•	•			
TRITEX TD								
737 TOP1	201	189	•	•	•			•
745 TOP1	168	185	•	•	•			•
10106 S a TOP3	294	275	•	•	•			•
TRITEX TT								
545 B*	140	134	•	•	•	•		
747 b E	181	188	•	•	•	•		
777 B*	251	213	•	•	•	•		
838 B	215	165	•	•	•	•		
838 E	215	204	•	•	•	•		
 Flexo	 Offset	 UV-Flexo / UV-Offset						
 Thermo Transfer	 Thermo Direkt	 Trockentoner (z.B. Laser)						

* Sonderausführung auf Anfrage.