







Qualität	Grammatur (g/m <sup>2</sup> )	Stärke (µm)	Bedruckbarkeit					
								
<b>TRITEX L</b>								
5085 BQ*	196	130			•	•		
515 a	132	141	•	•	•		•	
525 a	137	148	•	•	•		•	
555	175	175	•	•	•		•	
575	210	205	•	•	•		•	
5105	245	225	•	•	•		•	
101010*	345	342	•	•	•		•	
<b>TRITEX SD</b>								
242 a*	97	111	•	•	•			
535*	137	160	•	•	•			
545	141	165	•	•	•			
7087*	166	135	•	•	•			
747*	181	212	•	•	•			
<b>TRITEX TD</b>								
737 TOP1	201	189	•	•	•		•	
745 TOP1	168	185	•	•	•		•	
10106 S a TOP3	294	275	•	•	•		•	
<b>TRITEX TT</b>								
747 b E	181	188	•	•	•	•		
838 B	215	165	•	•	•	•		
838 E	215	204	•	•	•	•		
848 b B*	202	182	•	•	•	•		
878 a B*	272	214	•	•	•	•		

 Flexo	 Offset	 UV-Flexo / UV-Offset
 Thermo Transfer	 Thermo Direkt	 Trockentoner (z. B. Laser)

\*Sonderausführung auf Anfrage.