







Qualität	Grammatur (g/m ²)	Stärke (µm)	Bedruckbarkeit									
												
TRITEX L												
515 a	132	148	•	•	•					•		
525 b	137	148	•	•	•					•		
555 a	175	168	•	•	•					•		
575 a	210	205	•	•	•					•		
5105 a	245	225	•	•	•					•		
757 b*	215	180										
101010 a*	345	342	•	•	•					•		
TRITEX SD												
242 a*	97	111	•	•	•							
535 a*	137	160	•	•	•							
545 c	141	165	•	•	•							
7087 b*	166	137	•	•	•							
747 c*	181	212	•	•	•							
TRITEX TD												
737 a TOP1	201	189	•	•	•					•		
745 a TOP1	168	185	•	•	•					•		
7411 a TOP1*	228	228	•	•	•					•		
71020 TOP1*	421	360	•	•	•					•		
10106 S a TOP3	294	275	•	•	•					•		
TRITEX TT												
747 c E	181	185	•	•	•	•						
838 B	215	165	•	•	•	•						
838 a E	216	204	•	•	•	•						
848 b B*	202	182	•	•	•	•						
878 a B*	272	214	•	•	•	•						



Flexo



Offset



UV-Flexo / UV-Offset



Thermo Transfer



Thermo Direkt



Trockentoner (z. B. Laser)

*Sonderausführung auf Anfrage.